

tesa® 4325

General purpose masking tape

PRODUCT INFORMATION

Product Description

tesa® 4325 is a finely creped paper masking tape with a natural rubber adhesive

Main Application

The product is suitable for general purpose applications:

- masking
- holding
- sealing
- fixing
- light duty packaging etc.

Technical Data

■ Backing material	slightly-creped paper	■ Adhesion to steel	2.6 N/cm
■ Total thickness	120 µm	■ Elongation at break	10 %
■ Type of adhesive	natural rubber	■ Tensile strength	33 N/cm

Properties

■ Hand tearability	++	■ Sharp colour edge	+
■ Paint anchorage	++		

Evaluation across relevant tesa® assortment: ++ very good, + good, o medium, - low

For latest information on this product please visit <http://l.tesa.com/?ip=04325>

Page 1 of 1 / As of 12/19/14

tesa SE

Quickbornstraße 24
20253 Hamburg
Germany
Phone: +49 (40) 4909 101

tesa SE
A Beiersdorf Company

www.tesa.com

tesa tape inc.

5825 Carnegie Boulevard
Charlotte, N.C. 28209
United States of America
Phone: +1 (704) 554 0707
Fax: +1 (704) 553 5634
www.tesatape.com

tesa tape Asia Pacific Pte. Ltd.

9 North Buona Vista Drive
#04-01 The Metropolis
Tower 1
Singapore 138588
Tel: +65 6697 9888
Fax: +65 6659 6390
www.tesa-asia.com

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.