

Tipologia Produttiva : **Monocottura da Rivestimento**

Productive Typologies: **Single Fired Wall tiles**

Formati / Sizes : **20x50 (8"x20") - 10x50 (4"x20")**












Superficie: **Satinata**

Finish: **Satin**

Bordi / Edges: **Naturale / Natural**



ISO 13006 UNI EN 14411 - APPENDICE L - BIII

CARATTERISTICHE TECNICHE	NORMA		CHIC
 spessore thickness épaisseur Stärke	10545.2	± 10 %	11 mm
 lunghezza e larghezza length and width longueur et largeur Länge und Breite		± 0,3 %	± 0,3 %
 rettezza degli spigoli straightness of sides rectilignité des arêtes Kantengeradheit		± 0,3 %	± 0,3 %
 ortogonalità wedging orthogonalité Rechtwinkligkeit		± 0,3 %	± 0,3 %
 planarità flatness planéité Ebenflächigkeit		+0,8mm -0,2mm	+0,8mm -0,2mm
 assorbimento d'acqua water absorption absorption d'eau Wasseraufnahme	10545.3	valore medio > 10%	valore medio > 10%
 resistenza alla flessione bending strength résistance à la flexion Biegefestigkeit	10545.4	spessore ≥ 7,5mm - 15 N/mm ² minimo	15 N/mm ²
sforzatura (S) breaking strength (S) chargement de rupture (S) Bruchlast (S)		spessore ≥ 7,5mm - 600 N minimo	600 N
 resistenza al cavillo crazing resistance résistance au tressailage Harrißbeständigkeit	10545.11	richiesta required demandée Erforderlich	garantita guaranteed garantie Garantiert
 resistenza ai prodotti chimici di uso domestico e additivi per piscina resistance to household chemicals and swimming-pool additives résistance aux produits chimiques d'usage domestique et additifs pour piscine Beständigkeit gegen Haushaltschemikalien und Badwasserzusätze für Schwimmbäder	10545.13	GB minimo	GA
 resistenza all'attacco acido e basico acid and alkali resistance résistance aux acides et aux bases Widerstand gegen Säuren and Laugen		Secondo la classificazione indicata dal fabbricante As per the producer's internal classification Selon la classification mentionnée par le fabricant Laut vom Hersteller angegebener Klassifizierung	GLA - GHA
 resistenza alle macchie stain resistance résistance aux taches Fleckenfestigkeit	10545.14	Classe 3 minimo	Classe 5