

Tipologia Produttiva : **Monocottura da Rivestimento**  
 Productive Typologies: **Single Fired Wall tiles**

Formati / Sizes : **20x33,3 ( 8"x13" ) - 10x33,3 ( 4"x13" )**

Superficie: **Satinata**  
 Finish: **Satin**

Bordi / Edges: **Naturale / Natural**



**ISO 13006 UNI EN 14411 - APPENDICE L - BIII**

CARATTERISTICHE TECNICHE	NORMA		LES ARTS
 <b>spessore</b> thickness épaisseur Stärke	10545.2	± 10 %	<b>9,5 mm</b>
 <b>lunghezza e larghezza</b> length and width longueur et largeur Länge und Breite		± 0,3 %	<b>± 0,3 %</b>
 <b>rettilineità degli spigoli</b> straightness of sides rectilignité des arêtes Kantengeradheit		± 0,3 %	<b>± 0,3 %</b>
 <b>ortogonalità</b> wedging orthogonalité Rechtwinkligkeit		± 0,3 %	<b>± 0,3 %</b>
 <b>planarità</b> flatness planéité Ebenflächigkeit		+0,8mm -0,2mm	<b>+0,8mm -0,2mm</b>
 <b>assorbimento d'acqua</b> water absorption absorption d'eau Wasseraufnahme	10545.3	valore medio > 10%	<b>valore medio &gt; 10%</b>
 <b>resistenza alla flessione</b> bending strength résistance à la flexion Biegefestigkeit	10545.4	spessore ≥ 7,5mm - 15 N/mm <sup>2</sup> minimo	<b>15 N/mm<sup>2</sup></b>
<b>sforzamento di rottura (S)</b> breaking strength (S) chargement de rupture (S) Bruchlast (S)		spessore ≥ 7,5mm - 600 N minimo	<b>600 N</b>
 <b>resistenza al cavillo</b> crazing resistance résistance au tressillage Harrißbeständigkeit	10545.11	richiesta required demandée Erforderlich	<b>garantita</b> guaranteed garantie Garantiert
 <b>resistenza ai prodotti chimici di uso domestico e additivi per piscina</b> resistance to household chemicals and swimming-pool additives résistance aux produits chimiques d'usage domestique et additifs pour piscine Beständigkeit gegen Haushaltschemikalien und Badewasserzusätze für Schwimmbäder	10545.13	GB minimo	<b>GA</b>
 <b>resistenza alle macchie</b> stain resistance résistance aux taches Fleckenfestigkeit	10545.14	Classe 3 minimo	<b>Classe 5</b>