

Tipologia Produttiva : **Monocottura da Rivestimento**
 Productive Typologies: **Single Fired Wall tiles**












Formati / Sizes : **20x50** (8"x20")

Superficie: **Satinata**
 Finish: **Satin**

Bordi / Edges: **Naturale / Natural**

ISO 13006 UNI EN 14411 - APPENDICE L - BIII



| CARATTERISTICHE TECNICHE | NORMA | | TREND |
|--|----------|---|---|
|  spessore thickness épaisseur Stärke | 10545.2 | ± 10 % | 11 mm |
|  lunghezza e larghezza length and width longueur et largeur Länge und Breite | | ± 0,3 % | ± 0,3 % |
|  rettilineità degli spigoli straightness of sides rectilignité des arêtes Kantengeradheit | | ± 0,3 % | ± 0,3 % |
|  ortogonalità wedging orthogonalité Rechtwinkligkeit | | ± 0,3 % | ± 0,3 % |
|  planarità flatness planéité Ebenfächigkeit | | +0,8mm -0,2mm | +0,8mm -0,2mm |
|  assorbimento d'acqua water absorption absorption d'eau Wasseraufnahme | 10545.3 | valore medio > 10% | valore medio > 10% |
|  resistenza alla flessione bending strength résistance à la flexion Biegefestigkeit | 10545.4 | spessore ≥ 7,5mm - 15 N/mm ² minimo | 15 N/mm ² |
| sforzatura di rottura (S) breaking strength (S) chargement de rupture (S) Bruchlast (S) | | spessore ≥ 7,5mm - 600 N minimo | 600 N |
|  resistenza al cavillo crazing resistance résistance au tressillage Harrißbeständigkeit | 10545.11 | richiesta required demandée Erforderlich | garantita guaranteed garantie Garantiert |
|  resistenza ai prodotti chimici di uso domestico e additivi per piscina resistance to household chemicals and swimming-pool additives résistance aux produits chimiques d'usage domestique et additifs pour piscine Beständigkeit gegen Haushaltschemikalien und Badewasserzusätze für Schwimmbäder | 10545.13 | GB minimo | GA |
|  resistenza all'attacco acido e basico acid and alkali resistance résistance aux acides et aux bases Widerstand gegen Säuren and Laugen | | Secondo la classificazione indicata dal fabbricante As per the producer's internal classification Selon la classification mentionnée par le fabricant Laut vom Hersteller angegebener Klassifizierung | GLA - GHA |
|  resistenza alle macchie stain resistance résistance aux taches Fleckenfestigkeit | 10545.14 | Classe 3 minimo | Classe 5 |