



11190 NW 25th Street, Suite 100
 MIAMI, FL 33172
 www.rocatileusa.com

Ceramic tiles, dry pressed, for internal and external floorings

Model/ Series: STATUARY Matte
Size: All Sizes Available
Colors: All Colors Available
Type: GLAZED PORCELAIN
Thickness: All sizes: 8.5 mm, except: 8"x48" & 24"x48", 10 mm

<u>Technical Data</u>	<u>ASTM</u>	<u>ISO</u>	<u>Value Required ANSI</u>	<u>Declared ASTM</u>
Water Absorption	C373	ISO-10545/3	<=3%	<=0.5%
Break Strength	C648	ISO-10545/4	>= 250	Min. 350
Scratch Hardness	MOH's Scale	EN-101	-	5
Chemical Resistance	C650	ISO-10545/13	Unaffected	Unaffected
Frost Resistance	C1026	ISO-10545/12	Resistant	Resistant
Group	C1027	ISO-10545/7	-	4
Minimum Bond Strength (PSI)	C482	-	>=50 psi	165
Coefficient of Friction/dry	C1028	-	Varies	N/A
Coefficient of Friction/wet	C1028	-	Varies	N/A
Dynamic Coefficient of Friction (DCOF)	A137.1	-	>=0.42	>=0.51
Shade and Texture Rating	CTDA "V"	-	-	V3
Facial Dimensions	C499	ISO-10545/2	1.5% Max	Pass
Range of Thickness	C499	ISO-10545/2	0.040 Max	Pass
Warpage	C485	ISO-10545/2	0.75%	Pass
Wedging	C502	ISO-10545/2	1.0% Max	Pass

Signature:
 Quality Management Manager

Release Date 7/29/2016





11190 NW 25th Street, Suite 100
 MIAMI, FL 33172
 www.rocatileusa.com

Ceramic tiles, dry pressed, for internal and external floorings

Model/ Series: STATUARY POLISHED
Size: All Sizes Available
Colors: All Colors Available
Type: POLISHED PORCELAIN
Thickness: 9.5 mm (12x24R & 24x24R) / 11.5 mm (24x48R & 8x48R)

<u>Technical Data</u>	<u>ASTM</u>	<u>ISO</u>	<u>Value Required</u> <u>ANSI</u>	<u>Declared</u> <u>ASTM</u>
Water Absorption	C373	ISO-10545/3	<=0.5%	<=0.1%
Break Strength	C648	ISO-10545/4	>= 250	Min. 350
Scratch Hardness	MOH's Scale	EN-101	-	4
Chemical Resistance	C650	ISO-10545/13	Unaffected	Unaffected
Frost Resistance	C1026	ISO-10545/12	Resistant	Resistant
Group	C1027	ISO-10545/7	-	4
Minimum Bond Strength (PSI)	C482		>=50 psi	165
Coefficient of Friction/dry	C1028	-	Varies	>=0.60
Coefficient of Friction/wet	C1028	-	Varies	>=0.5
Dynamic Coefficient of Friction (DCOF)	A137.1	-	>=0.42	>=0.35
Shade and Texture Rating	CTDA "V"	-	-	V2
Facial Dimensions	C499	ISO-10545/2	1.5% Max	Pass
Range of Thickness	C499	ISO-10545/2	0.040 Max	Pass
Warpage	C485	ISO-10545/2	0.75%	Pass
Wedging	C502	ISO-10545/2	1.0% Max	Pass

Signature:
 Quality Management Manager

Release Date 07/21/2017

