



plank
project

ermes aurelia



plankwood

Tre essenze di legno dallo stile rustico, abbinabili tra loro in una combinazione di grande effetto e con gli inserti colorati del decoro MIX.

Three different essences of rustic wood, that can create a floor or feature wall of great effect, with the addition of the colorful decoro MIX.

Drei wertvolle Holzarten mit rustikalem Stil, die sich perfekt miteinander kombinieren lassen und in Kombination mit dem DECORO MIX ein einzigartiges Effekt bieten

Style rustique en trois types de bois qui se combinent entre eux et qui donnent un grand effet, enrichie par les inserts colorés du décor MIX.

gres porcellanato
porcelain stoneware
feinsteinzeug
grès cérame




14x83



plankwood

BLEND 14x83







ACERO 14x83
decoro MIX 12x14 - 6x14 - 3x14



plankwood

| PEI V | V4 |

mosaico: | A+B+C |

grip: | R12 | A+B+C |

NOCE




FRASSINO



ACERO



BLEND



14x83

36823 f60 | MQ

36822 f60 | MQ

36821 f60 | MQ

36824 f60 | MQ

14x83
GRIP

36823/G f65 | MQ

36822/G f65 | MQ

36821/G f65 | MQ


DECORI . DECORS . DEKORE



3/6/12x14
decoro MIX

37171


f80 | CP



MOSAICI . MOSAICS . MOSAIKEN . MOSAÏQUES


3,5x3,5
mosaico

NOCE




37066 i25 | MQ

FRASSINO




37065 i25 | MQ

ACERO



37064 i25 | MQ

BLEND



37067 i25 | MQ

PEZZI SPECIALI
SPECIAL ITEMS
FORMSTÜCKE
PIÈCES SPÉCIALES



battiscopa
7x83

c30 | PZ

ACERO	36832
FRASSINO	36833
NOCE	36834

IMBALLI E PESI

PACKING - WEIGHTS
VERPACKUNG - GEWICHT
EMBALLAGES - POIDS



BOX














PALLET

	mm	pcs	m ²	kg	box	m ²	kg
14x83	10	13	1,51	32,50	40	60,40	1.300
3,5x3,5 mosaico	10	13	-	20	-	-	-



Classificazione secondo norme CEN gruppo B1a UNI EN 14411 App. G - GI
 Classification in accordance with CEN standards B1a UNI EN 14411 App. G - GI
 Klassifizierung gemäß CEN Normen Gruppe B1a UNI EN 14411 App. G - GI
 Classification selon les normes CEN groupe B1a UNI EN 14411 App. G - GI

Caratteristiche tecniche
 Caracteristiques Techniques
 Technische Eigenschaften
 Technical Features

	Proprietà fisico-chimiche Physical-chemical properties Pysich-chemische Eigenschaften Propriétés physico-chimiques	Tipo di prova Standard of test Testnorm Norme du test	Valore prescritto Required value Vorgeschriebener Wert Valeur prescrite	Valore Ermes Aurelia Ermes Aurelia standards Ergebnis Ermes Aurelia Valeur Ermes Aurelia
	Lunghezza e larghezza Length and width Länge und Breite Longueur et largeur	UNI EN ISO 10545.2	± 0,6%	Conforme In accordance Erfüllt Conforme
	Ortogonalità Wesigung Rechtwinkligkeit Orthogonalité	UNI EN ISO 10545.2	± 0,6%	Conforme In accordance Erfüllt Conforme
	Spessore Thickness Stärke Epaisseur	UNI EN ISO 10545.2	± 5%	Conforme In accordance Erfüllt Conforme
	Planarità Warpage Ebenföchigkeit Planéité	UNI EN ISO 10545.2	± 0,5%	Conforme In accordance Erfüllt Conforme
	Rettilineità spigoli Linearity Kantengeradheit Rectitude des arêtes	UNI EN ISO 10545.2	± 0,5%	Conforme In accordance Erfüllt Conforme
	Assorbimento d'acqua Water Absorption Wasseraufnahme Absorption d'eau	UNI EN ISO 10545.3	≤ 0,5%	Conforme In accordance Erfüllt Conforme
	Coefficiente di dilatazione termica lineare Coefficient of linear thermal-expansion Lineare Wärmeausdehnung Coefficient linéaire de dilatation thermique	UNI EN ISO 10545.8	-	7MK ⁻¹
	Resistenza a flessione Flexion Resistance Biegezugfestigkeit Résistance à la flexion	UNI EN ISO 10545.4	≥ 35 N/mm ²	Conforme In accordance Erfüllt Conforme
	Resistenza agli sbalzi termici Thermal shock resistance Temperaturwechselbeständigkeit Résistance aux écarts de température	UNI EN ISO 10545.9	Richiesta Required Requise Erforderlich	Resistente Resistant Résistants Widerstandsfähig
	Resistenza al gelo Frost resistance Frostwiderstandsfähigkeit Résistance au gel	UNI EN ISO 10545.12	Richiesta Required Requise Erforderlich	Resistente Resistant Résistants Widerstandsfähig
PEI	Resistenza all'abrasione superficiale Resistance to surface abrasion Widerstand gegen tiefenabrieb Résistance à l'abrasion superficielle	UNI EN ISO 10545.7	Secondo quanto dichiarato dal fabbricante As the manufacturer declaration Selon chiffre d'affaire déclaré par le fabricant Nach dem, was der Hersteller angegeben hat	Indicata sul catalogo Indicated on the catalogue Im prospekt angegeben Indique sur le catalogue
	Resistenza allo scivolamento Slip resistance Rutschfestigkeit Résistance à la glissance	DIN 51130	USA test 	Indicata sul catalogo Indicated on the catalogue Im prospekt angegeben Indique sur le catalogue
		ASTM C1028		Indicata sul catalogo Indicated on the catalogue Im prospekt angegeben Indique sur le catalogue

ermes aurelia

ermes aurelia

ermesceramichespa

via statale 467, n.171 . 42013 veggia (re) - italy . tel. +39 0536 991511 . fax +39 0536 824777

e-mail: info@ermes-ceramiche.it . www.ermes-ceramiche.it

